

Donaldson®  
Torit®

**UNIMASTER®  
DUST COLLECTORS**



# FILTRATION ENGINEERED FOR PERFORMANCE

The Unimaster dust collector from Donaldson® Torit® is designed to maximize dust collection and the life of collector components for years of extended service. In production for over 40 years, the Unimaster collector's compact design and quiet operation is an industry success. Yet, Donaldson Torit is continually improving the Unimaster to ensure that it provides efficient, trouble-free service.

A self-contained collector with everything needed to begin collecting dust, the Unimaster comes complete with fan and fan motor, automatic shaker and shaker motor, and system controller making installation quick and easy. Since the automatic shaker cleans the bag filters, there is no need for expensive compressed air. Ideal for intermittent operations in plant processes, the Unimaster can be used as a central system or at the point of dust generation.

## THE UNIMASTER FEATURES:

### COMPACT DESIGN

Minimizes floor space and fits in virtually any plant layout.

### VERSATILITY

Three configurations to suit a variety of dust collection applications.

### BROAD RANGE

Offering maximum air handling capacity in a compact design, the Unimaster offers filtration media area from 40 to 750 square feet.

### QUIET & EFFICIENT OPERATION

Motors and fan are enclosed in collector housing to minimize noise.



### EASY MAINTENANCE

### 10-YEAR WARRANTY



**40** YEARS  
OF  
**PROVEN**  
PERFORMANCE

# SIZES & OPERATIONS



\* Doors not shown on unit for illustrative purposes.

## UNIMASTER PERFORMANCE:

### PERFORATED INLET DEFLECTOR

Knocks down larger particles into the hopper reducing bag abrasion and increasing bag filter life

### QUICK-RELEASE LEVER

Allows for easy removal and maintenance of bin

### HEAVY-DUTY FLEXIBLE METAL COILS

Inserted into filter bags keeps bags open to maximize airflow and assist in knocking dust off during cleaning cycle

### BAG-RELEASE LEVERS

Allow for easy removal of bags



Perforated Inlet Deflector



Quick-Release Lever




Heavy-Duty Flexible Metal Coils




Bag-Release Levers

# DIMENSIONS & SPECIFICATIONS


## HOPPER BASE




Front View  
UMA 40 Shown



Front View  
UMA 70-250  
(UMA 70 Shown)




Front View  
UMA 450-750  
(750 Shown)




Right Side View  
UMA 450-750  
(750 Shown)


## BIN VENT BASE (H-TYPE)




Front View  
UMA 40 Shown



Front View  
UMA 70-250  
(UMA 70 Shown)




Front View  
UMA 450-750  
(750 Shown)




Right Side View  
UMA 450-750  
(750 Shown)


## 55-GALLON DRUM BASE




Front View  
UMA 150-250  
(UMA 150 Shown)



Side View  
UMA 150-250  
(UMA 150 Shown)



Front View  
UMA 450-750  
(750 Shown)



Right Side View  
UMA 450-750  
(750 Shown)

Model	Nominal Airflow Range*		Cloth Area		No. of Bag Filters	No. of Bins/ Drums**	Inlet Diameter		Shipping Weight					
	cfm	m³/h	ft²	m²			in	mm	Hopper Base		Bin Vent Base		55-Gallon Drum Base	
									lb	kg	lb	kg	lb	kg
40	120-400	204-679	40	3.7	1	1	4	101.6	250	113.4	260	117.9	N/A	N/A
70	200-525	340-892	70	6.5	1	1	4	101.6	450	204.1	320	145.1	N/A	N/A
100	200-1,000	340-1,699	100	9.3	1	1	8	203.2	600	272.2	440	199.6	N/A	N/A
150	450-2,000	764-3,397	150	13.9	1	1	8	203.2	800	362.9	600	272.2	875	396.9
250	450-3,000	764-5,096	244	22.7	1	1	10	254.0	1,155	523.9	700	317.5	1,265	573.8
450	1,350-5,000	2,293-8,493	444	41.2	2	2	12	304.8	1,840	834.6	1,415	641.8	1,830	830.1
750	2,000-10,000	3,397-16,987	750	69.7	2	2	14	355.6	2,355	1,068.2	1,800	816.5	2,345	1,063.7

\* Based on clean filter.

\*\* UMA 40 uses one 0.75 cu ft bin; UMA 70 uses one 2 or 3 cu ft bin (for 3 cu ft bin, add 9-in to height); UMA 100-250 uses one 3 cu ft bin; and UMA 450-750 uses two 3 cu ft bins. 55-Gallon drum base available on UMA 150-750. UMA 150-250 uses one drum and UMA 450-750 uses two drums (drums not included).

Model	Dimensions																								
	A		B		C		D		E		F		G		H		J		K		L		M		
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	
40	17.6	447.0	27.6	701.0	17.6	447.0	61.2	1554.5	20.3	515.6	28.9	734.1	20.3	515.6	41.5	1054.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
70	23.2	589.3	32.7	830.6	28.7	729.0	79.3	2014.2	25.4	645.2	33.8	858.5	25.4	645.2	49.5	1257.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
100	32.8	833.1	41.2	1046.5	28.8	731.5	83.8	2128.5	32.3	820.4	41.2	1046.5	25.4	645.2	49.5	1257.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
150	32.3	820.4	41.2	1046.5	36.4	924.6	94.0	2387.6	32.3	820.4	41.2	1046.5	32.9	835.7	59.8	1518.9	32.9	835.7	41.6	1056.6	30.3	769.6	121.0	3073.4	
250	32.7	830.6	56.2	1427.5	36.4	924.6	104.8	2661.9	32.3	820.4	56.2	1427.5	32.9	835.7	62.2	1579.9	47.8	1214.1	56.6	1437.6	32.9	835.7	129.1	3279.1	
450	45.7	1160.8	71.7	1821.2	44.3	1125.2	121.1	3075.9	63.0	1600.2	71.6	1818.6	40.9	1038.9	80.6	2047.2	59.8	1518.9	70.1	1780.5	38.1	967.7	148.4	3769.4	
750	76.5	1943.1	88.3	2242.8	52.1	1323.3	125.4	3185.2	79.6	2021.8	88.3	2242.8	49.1	1247.1	85.3	2166.6	76.2	1935.5	86.5	2197.1	47.4	1204.0	150.2	3815.1	

## UMA WEIGHTED SOUND PRESSURE LEVELS

Model	40	70	100	150	250	450	750
With acoustic diffuser* dB(A)	71	70	71	74	74	82	79
Without acoustic diffuser dB(A)	78	N/A**	N/A**	N/A**	N/A**	N/A**	N/A**

Above dB(A) sound levels are an average of measurements taken in a normal industrial area. Sound levels were taken in accordance with Reference Standard ISO 3746:1995, Survey Method, Grade 3. Installed sound levels may vary depending upon measurement location, operating conditions, and installations.

\*Sound ratings on UMA 40, 70, 80, 150 and 450 are with the largest available fan. UMA 250 sound rating is with 5 HP K7 fan. UMA 750 sound rating is estimated for the 30 hp TBI fan. For specific fan models, contact Donaldson Torit.


\*\*Acoustic diffuser (silencer) is standard on UMA 70, 100, 150, 250, 450 and 750.

# PERFORMANCE SELECTIONS


## FLEXIBLE POWER OFFERINGS

The Unimaster offers a variety of power packs to better meet your precise needs. The system performance graphs below show available static performance at the collector inlet with clean filters.


**UMA 40 and UMA 70**




**UMA 100**




**UMA 150**




**UMA 250**



**UMA 450**



**UMA 750**



# STANDARD FEATURES & AVAILABLE OPTIONS

Collector Design	Std	Opt
Integral Fan and Fan Motor*	X	
Integral Shaker Motor*	X	
Acoustic Diffuser Silencer (70-750)	X	
Acoustic Diffuser Silencer (40)		X
Caster Pack		X
Weatherhood (weather bend) Roof		X
Various Inlet Locations		X
<b>Bag Filters</b>		
8 oz. (226.8 g) Polyester One-Piece Bag Filters	X	
Anti-Static Bag Filters		X
Variety of Bag Media Options		X
<b>Paint System</b>		
Textured Multi-Coat Paint Finish with 2,000-Hour Salt Spray Performance	X	
Custom Color		X

Hopper Discharge	Std	Opt
Bin Base with Quick Release Lever		X
55-Gallon (208.2-Liter) Drum Base		X
Bin Vent Base		X
<b>Electrical Controls, Gauges and Enclosures</b>		
Push-Button Controls	X	
Solid-State Timer in Type (NEMA /UL) 12 Enclosure	X	
Motor Starter	X	
Magnehelic <sup>®</sup> Gauge		X
<b>Safety Features</b>		
Explosion Vents		X
Sprinkler Taps		X
<b>Warranty</b>		
10-Year Warranty	X	

\* All 60 Hz motors 1 HP and above are compliant with EISA.  
 \*\* Magnehelic is a registered trademark of Dwyer Instruments, Inc.

## PROVEN PERFORMANCE ON HUNDREDS OF APPLICATIONS



**UMA 450 - Filtering Plastic from a CNC Machine**



**UMA 250 on a School Wood Shop Application**



## Industry-Leading Technology

- Advanced filtration technology for optimal performance
- Reduced energy consumption and cost of ownership
- Advanced design and testing capabilities

## The Most Filters and Parts

- For every brand and style of collector
- Wide range of filtration media for any application
- 90,000 filters and parts in stock and ready to ship

## Unparalleled Support

- Live technical specialists
- Comprehensive pre- and post-sale support
- 40 manufacturing plants and 14 distribution centers worldwide

Significantly improve the performance of your collector with genuine Donaldson Torit replacement filters and parts. **Call Donaldson Torit at 800-365-1331.**

### Important Notice

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.



Donaldson.

Donaldson Company, Inc.  
Minneapolis, MN  
[donaldson.com](http://donaldson.com) • [shop.donaldson.com](http://shop.donaldson.com)

**North America**  
Email: [donaldson@donaldson.com](mailto:donaldson@donaldson.com)  
Phone: (USA): +1-800-365-1331 • (MX): +1-800-343-36-39

**Australasia**  
Email: [marketing.australia@donaldson.com](mailto:marketing.australia@donaldson.com)  
Phone: +61-2-4350-2000  
Toll Free: (AU) +1800-345-837 • (NZ) +0800-743-387

F118044 ENG (02/20) Unimaster Dust Collector ©2004-2020 Donaldson Company, Inc.  
Donaldson, Torit, Unimaster and the color blue are marks of Donaldson Company, Inc. All other marks belong to their respective owners.

**China**  
Email: [info.cn@donaldson.com](mailto:info.cn@donaldson.com)  
Phone: +86-400-820-1038

**Donaldson Europe B.V.B.A.**  
Email: [IAF-europe@donaldson.com](mailto:IAF-europe@donaldson.com)  
Phone: +32-16-38-3811

**India**  
Email: [info.difs@donaldson.com](mailto:info.difs@donaldson.com)  
Phone: +91-124-4807-400 • +18001035018

**Japan**  
Email: [jp-ndl.jfsweb@donaldson.com](mailto:jp-ndl.jfsweb@donaldson.com)  
Phone: +81-42-540-4112

**Korea**  
Email: [iaf-kr@donaldson.com](mailto:iaf-kr@donaldson.com)  
Phone: +82-2-517-3333

**Latinoamerica**  
Email: [IndustrialAir@donaldson.com](mailto:IndustrialAir@donaldson.com)  
Phone: +52-449-300-2442

**South Africa**  
Email: [SAMarketing@donaldson.com](mailto:SAMarketing@donaldson.com)  
Phone: +27-11-997-6000

**Southeast Asia**  
Email: [IAF.SEA@donaldson.com](mailto:IAF.SEA@donaldson.com)  
Phone: +65-6311-7373