

DESIGN

- Design features 15 helix tubes constructed of Spunbond Polyester media laminated with ePTFE
- Multiple tube design increases surface area over similarly-sized envelope-style bags by 25%, effectively lowering the Air-to-Media Ratio
- Support cores inserted into outermost tubes with option for additional support cores for increased stability
- Reusable venturi is sold separately

FEATURES

- Up to 180° F continuous use
- Decreased Air-to-Media Ratio results in lower pressure drop and longer life
- Smooth surface of Spunbond Polyester and ePTFE membrane yields excellent dust release characteristics
- Advanced media is more efficient in capturing submicron dust particles (0.3 micron and larger), resulting in lower emissions
- Cleaner air, longer filter life, and greater cost savings
- Can be used in new installations or as a replacement filter for Donaldson Dalamatic bag and cage filter assemblies




HELIX TUBE RACK

CONSTRUCTION

HELIX TUBES	<ul style="list-style-type: none"> • 1.02" (26.0mm) nominal diameter • Spunbond Polyester with ePTFE membrane • Spirally formed hot air weld seam
SUPPORT CORES	Polypropylene
TOP	Injection molded PA6 nylon
BOTTOM	Hard polyurethane
GASKET	Polyethylene

CONFIGURATIONS

DALAMATIC MODEL	TUBE LENGTH		OVERALL LENGTH		FILTER AREA	
	IN	MM	IN	MM	FT ²	M ²
DLMV & DLMC 0.7 m	27.5	700	27.7	704	9.2	0.9
DLMV & DLMC 1.0 m	39.4	1,000	39.6	1,006	13.2	1.3
DLMV & DLMC 1.25 m	49.2	1,240	49.4	1,247	16.5	1.6
DLMV & DLMC 1.5 m	59.1	1,500	59.3	1,507	19.7	1.9



Significantly improve the per parts. **Call Donaldson Torit**

Torit replacement filters and

Important Notice

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.



Donaldson Company, Inc.
 Minneapolis, MN
donaldsontorit.com • shop.donaldson.com

North America
 Email: donaldsontorit@donaldson.com
 Phone: (USA): +1-800-365-1331 • (MX): +1-800-343-36-39

Australasia
 Email: marketing.australia@donaldson.com
 Phone: +61-2-4350-2000
 Toll Free: (AU) +1800-345-837 • (NZ) +0800-743-387

F118149 ENG (02/20) Helix Tube Rack ©2014-2020 Donaldson Company, Inc.

Donaldson, Torit, Dalamatic and the color blue are marks of Donaldson Company, Inc. All other marks belong to their respective owners.

China
 Email: info.cn@donaldson.com
 Phone: +86-400-820-1038

Donaldson Europe B.V.B.A.
 Email: IAF-europe@donaldson.com
 Phone: +32-16-38-3811

India
 Email: info.difs@donaldson.com
 Phone: +91-124-4807-400 • +18001035018

Japan
 Email: jp-ndli.ifsw@donaldson.com
 Phone: +81-42-540-4112

Korea
 Email: iaf-kr@donaldson.com
 Phone: +82-2-517-3333

Latinoamerica
 Email: IndustrialAir@donaldson.com
 Phone: +52-449-300-2442

South Africa
 Email: SAMarketing@donaldson.com
 Phone: +27-11-997-6000

Southeast Asia
 Email: IAFSEA@donaldson.com
 Phone: +65-6311-7373